

Original SCHNORR® safety washers type "VS" material X5CrNi18-10 (1.4301)

Article number/ Order reference	Size		Ordering dimensions					Packaging	
	Nominal size		d ₁	d ₂	s	h _{min.}	h _{max.}	Unit	Weight
	[mm]	[Inch]	[mm]	[mm]	[mm]	[mm]	[mm]	[pcs.]	per 1000 pieces [kg]
416 201	5	3/16"	5.3	9.0	1.0	1.05	1.3	1000	0.298
418001	6		6.4	10.0	1.0	1.10	1.4	1000	0.330
422 901	8	5/16"	8.4	13.0	1.5	1.60	2.0	1000	0.836
425 020	10	3/8"	10.5	16.0	1.8	1.90	2.3	1000	1.501
427 700	12		13.0	18.0	1.8	1.90	2.4	500	1.731
430 660	14		15.0	22.0	1.8	1.95	2.5	500	2.693
430 750	16	5/8"	17.0	24.0	2.5	2.60	3.1	250	4.145
433 621	18		19.0	27.0	2.5	2.65	3.2	250	5.337
435 250	20		21.0	30.0	2.5	2.70	3.3	250	6.709
436 721	22		23.0	33.0	2.5	2.70	3.4	100	8.184
438 021	24		25.4	36.0	3.0	3.20	3.9	100	11.262
441 420	27		28.6	39.0	3.0	3.30	4.0	100	12.360
441 621	30	1 1/8"	31.6	45.0	3.0	3.55	4.3	100	18.222

We would be glad to offer you safety washers type "VS" in further special material grades on request.

Original SCHNORR® safety washers „UV“ captive fitting on bolts

For screws with captive safety washers

These safety washers are dimensioned so they can be fitted to bolts or screws from M2.5 to M10. This is done prior to thread rolling so the safety washers are captive.

